

➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties APA30uXS	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	<i>Preliminary data</i>	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	30	27	39
Blocked force	Quasistatic excitation, blocked-free	N	3.3	2.6	4.0
Stiffness	Quasistatic excitation, blocked-free	N/μm	0.11	0.09	0.12
Resonance frequency (free-free)	Harmonic excitation, free-free, on the admittance curve	Hz	26350	22398	28985
Response time (free-free)		ms	0.02	0.02	0.02
Resonance frequency (blocked-free)	Harmonic excitation, blocked-free, on the admittance curve	Hz	4770	4055	5247
Response time (blocked-free)		ms	0.10	0.09	0.12
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	0.05	0.05	0.07
Max. no load displacement at resonance	Max. harmonic excitation, free-free	μm p-p	24	19	29
Max. voltage at resonance	Max. harmonic excitation, free-free	Vrms	9.00	7.20	10.80
Resolution	Quasistatic excitation	nm	0.30	-	-
Height (in actuation direction)		mm	3.90	3.80	4.00
Length		mm	8.60	8.50	8.70
Width (excl. wedge & wires)		mm	2.50	2.45	2.55
Width (incl. wedge & wires)		mm	5.00	4.00	6.50
Mass		g	0.15	-	-
Standard mechanical interface	2 flat surfaces 1*2.5 mm ²	-	-	-	-
Standard electrical interface	2 PFTE insulated AWG32 wires 80 mm long with Ø 1 banana plug	-	-	-	-

➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

Free-free	: The actuator is not fixed
Blocked-free	: The actuator is fixed to a mechanical support assumed infinitely stiff
Quasistatic excitation	: AC voltage between -20 and 150 V at 1 Hz
Harmonic excitation	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
Max. harmonic excitation	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
Displacement measurement	: Laser interferometer, capacitive displacement sensor
Admittance measurement	: HP 4194 A electrical impedance analyser
Environment	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

➤ MECHANICAL INTERFACE

- | | | |
|---|---|---|
| <input checked="" type="checkbox"/> [FI] Flat Interface | <input type="checkbox"/> [H] Flat Interface with hole | <input type="checkbox"/> [TH] Flat Interface with threaded hole |
| <input type="checkbox"/> [SV] Specific version | <input type="checkbox"/> [FF] Free-free Interface | <input type="checkbox"/> [SI] Specific interface |

➤ AVAILABLE OPTIONS

- | | | |
|--|---|--|
| <input type="checkbox"/> [SG] Strain gauges | <input type="checkbox"/> [ECS] Eddy current displacement sensor | <input checked="" type="checkbox"/> [NM] Non-magnetic sensor |
| <input checked="" type="checkbox"/> [VAC] Vacuum | | |