

CEDRAT  
TECHNOLOGIES  
15 chemin de Malacher  
ZIRST  
38246 MEYLAN Cedex  
France  
  
Tel. : +33 4 76 90 50 45  
Fax : +33 4 56 38 08 30  
<http://www.cedrat.com>  
[actuator@cedrat.com](mailto:actuator@cedrat.com)

## ➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties APA400MML	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	Preliminary data	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	364	328	473
Blocked force	Quasistatic excitation, blocked-free	N	189	151	227
Stiffness	Quasistatic excitation, blocked-free	N/μm	0,52	0,42	0,57
Resonance frequency (free-free)	Harmonic excitation, blocked-free, on the admittance curve	Hz	2738	2327	3012
Response time (free-free)		ms	0,18	0,16	0,21
Resonance frequency (blocked-free)	Harmonic excitation, free-free, on the admittance curve	Hz	634	539	697
Response time (blocked-free)		ms	0,79	0,71	0,91
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	10,00	9,00	13,00
Max. no load displacement at resonance	Max. harmonic excitation, free-free	μm p-p	291	233	349
Max. voltage at resonance	Max. harmonic excitation, free-free	Vrms	9,00	7,20	10,80
Resolution	Quasistatic excitation	nm	3,64	-	-
Height (in actuation direction)		mm	20,00	19,90	20,10
Length		mm	78,00	77,90	78,10
Width (excl. wedge & wires)		mm	10,00	9,95	10,05
Width (incl. wedge & wires)		mm	11,50	10,50	13,00
Mass		g	47,5	-	-
Standard mechanical interface	2 flat surfaces 6*10 mm <sup>2</sup> with M3 threaded hole	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG30 wires 100 mm long with Ø 1 banana plug	-	-	-	-

## ➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

<b>Free-free</b>	: The actuator is not fixed
<b>Blocked-free</b>	: The actuator is fixed to a mechanical support assumed infinitely stiff
<b>Quasistatic excitation</b>	: AC voltage between -20 and 150 V at 1 Hz
<b>Harmonic excitation</b>	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
<b>Max. harmonic excitation</b>	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
<b>Displacement measurement</b>	: Laser interferometer, capacitive displacement sensor
<b>Admittance measurement</b>	: HP 4194 A electrical impedance analyser
<b>Environment</b>	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

## ➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

## ➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

## ➤ MECHANICAL INTERFACE

- |  |   |  |
|--|---|--|
| <input type="checkbox"/> [ FI ] Flat Interface   | <input type="checkbox"/> [ H ] Flat Interface with hole | <input checked="" type="checkbox"/> [ TH ] Flat Interface with threaded hole |
| <input type="checkbox"/> [ SV ] Specific version | <input type="checkbox"/> [ FF ] Free-free Interface     | <input type="checkbox"/> [ SI ] Specific interface                           |

## ➤ AVAILABLE OPTIONS

- [ SG ] Strain gauges
- [ VAC ] Vacuum
- [ ECS ] Eddy Current proximity sensor
- [ NM ] Non-magnetic