

## ➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties APA500L	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	-	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	$\mu m$	500	450	650
Blocked force	Quasistatic excitation, blocked-free	N	570	456	684
Stiffness	Quasistatic excitation, blocked-free	N/ $\mu m$	1,14	0,91	1,25
Resonance frequency (free-free)	Harmonic excitation, blocked-free, on the admittance curve	Hz	1900	1710	2375
Response time (free-free)		ms	0,26	0,24	0,30
Resonance frequency (blocked-free)	Harmonic excitation, free-free, on the admittance curve	Hz	460	391	506
Response time (blocked-free)		ms	1,09	0,98	1,25
Capacitance	Quasistatic excitation, free-free, on the admittance curve	$\mu F$	40,00	36,00	52,00
Max. no load displacement at resonance	Max. harmonic excitation, free-free	$\mu m$ p-p	400	320	480
Max. voltage at resonance	Max. harmonic excitation, free-free	Vrms	9,00	7,20	10,80
Resolution	Quasistatic excitation	nm	5,00	-	-
Height (in actuation direction)		mm	55,00	54,90	55,10
Length		mm	145,00	144,90	145,10
Width (excl. wedge & wires)		mm	10,00	9,95	10,05
Width (incl. wedge & wires)		mm	16,00	15,00	17,50
Mass		g	200,0	-	-
Standard mechanical interface	2 flat surfaces 10*10 mm <sup>2</sup> with M5 threaded hole	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG30 wires 300 mm long with $\varnothing$ 1 banana plug	-	-	-	-

## ➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

<b>Free-free</b>	: The actuator is not fixed
<b>Blocked-free</b>	: The actuator is fixed to a mechanical support assumed infinitely stiff
<b>Quasistatic excitation</b>	: AC voltage between -20 and 150 V at 1 Hz
<b>Harmonic excitation</b>	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
<b>Max. harmonic excitation</b>	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
<b>Displacement measurement</b>	: Laser interferometer, capacitive displacement sensor
<b>Admittance measurement</b>	: HP 4194 A electrical impedance analyser
<b>Environment</b>	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

## ➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

## ➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

## ➤ MECHANICAL INTERFACE

- |                                                  |                                                         |                                                                              |
|--------------------------------------------------|---------------------------------------------------------|------------------------------------------------------------------------------|
| <input type="checkbox"/> [ FI ] Flat Interface   | <input type="checkbox"/> [ H ] Flat Interface with hole | <input checked="" type="checkbox"/> [ TH ] Flat Interface with threaded hole |
| <input type="checkbox"/> [ SV ] Specific version | <input type="checkbox"/> [ FF ] Free-free Interface     | <input type="checkbox"/> [ SI ] Specific interface                           |

## ➤ AVAILABLE OPTIONS

- [ SG ] Strain gauges
- [ CS ] Capacitive displacement sensor
- [ NM ] Non-magnetic
- [ VAC ] Vacuum