

## ➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties PPA40L	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	-	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	40	36	49
Blocked force	Quasistatic excitation, blocked-free	N	3500	2800	4200
Stiffness	Quasistatic excitation, blocked-free	N/μm	87,50	70,00	96,25
Resonance frequency (free-free)	Harmonic excitation, free-free, on the admittance curve	Hz	15500	13175	17050
Response time (free-free)	Harmonic excitation, free-free, on the admittance curve	ms	0,03	0,03	0,04
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	13,30	11,97	17,29
Max. tensile force	Static effort, blocked-free	N	1750	1313	1750
Resolution	Quasistatic excitation	nm	0,40	-	-
Height (in actuation direction)		mm	57,00	56,80	57,20
Depth (base)		mm	23,50	23,40	23,60
Width (base incl. wedge & wires)		mm	18,00	17,90	18,10
Mass		g	92,0	-	-
Standard mechanical interface (top)	1 centered M3 threaded hole 5 mm deep & 4 M2.5 threaded holes on Ø 15 mm 4 mm deep	-	-	-	-
Standard mechanical interface (base)	1 centered M3 threaded hole 5 mm deep & 4 M2.5 threaded holes on Ø 15 mm 4 mm deep	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG26 wires 100 mm long with Ø 1 banana plug	-	-	-	-

## ➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

<b>Free-free</b>	: The actuator is not fixed
<b>Blocked-free</b>	: The actuator is fixed to a mechanical support assumed infinitely stiff
<b>Quasistatic excitation</b>	: AC voltage between -20 and 150 V at 1 Hz
<b>Harmonic excitation</b>	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
<b>Max. harmonic excitation</b>	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
<b>Displacement measurement</b>	: Laser interferometer, capacitive displacement sensor
<b>Admittance measurement</b>	: HP 4194 A or Cypher C60 electrical impedance analyser
<b>Environment</b>	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

## ➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

## ➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

## ➤ MECHANICAL INTERFACE

- |  |   |  |
|--|---|--|
| <input type="checkbox"/> [ FI ] Flat Interface   | <input type="checkbox"/> [ H ] Flat Interface with hole | <input checked="" type="checkbox"/> [ TH ] Flat Interface with threaded hole |
| <input type="checkbox"/> [ SV ] Specific version | <input type="checkbox"/> [ FF ] Free-free Interface     | <input checked="" type="checkbox"/> [ SI ] Specific interface                |

## ➤ AVAILABLE OPTIONS

- [ SG ] Strain gauges
- [ ECS ] Eddy current displacement sensor
- [ NM ] Non-magnetic sensor
- [ VAC ] Vacuum