

➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties PPA80XL	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	-	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	90	81	104
Blocked force	Quasistatic excitation, blocked-free	N	7000	5600	8400
Stiffness	Quasistatic excitation, blocked-free	N/μm	77,78	62,22	85,56
Resonance frequency (free-free)	Harmonic excitation, free-free, on the admittance curve	Hz	8500	7225	9350
Response time (free-free)	Harmonic excitation, free-free, on the admittance curve	ms	0,06	0,05	0,07
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	48,00	43,20	62,40
Max. tensile force	Static effort, blocked-free	N	3500	2625	3500
Resolution	Quasistatic excitation	nm	0,90	-	-
Height (in actuation direction)		mm	100,00	99,80	100,20
Depth (base)		mm	30,00	29,80	30,20
Width (base incl. wedge & wires)		mm	30,00	29,80	30,20
Mass		g	319,0	-	-
Standard mechanical interface (top)	1 centered M5 threaded hole 6 mm deep & 4 M3 threaded holes on Ø 20 mm 6 mm deep	-	-	-	-
Standard mechanical interface (base)	1 centered M5 threaded hole 6 mm deep & 4 M3 threaded holes on Ø 20 mm 6 mm deep	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG26 wires 100 mm long with Ø 1 banana plug	-	-	-	-

➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

Free-free	: The actuator is not fixed
Blocked-free	: The actuator is fixed to a mechanical support assumed infinitely stiff
Quasistatic excitation	: AC voltage between -20 and 150 V at 1 Hz
Harmonic excitation	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
Max. harmonic excitation	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
Displacement measurement	: Laser interferometer, capacitive displacement sensor
Admittance measurement	: HP 4194 A or Cypher C60 electrical impedance analyser
Environment	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

➤ MECHANICAL INTERFACE

- | | | |
|--|---|--|
| <input type="checkbox"/> [F1] Flat Interface | <input type="checkbox"/> [H] Flat Interface with hole | <input checked="" type="checkbox"/> [TH] Flat Interface with threaded hole |
| <input type="checkbox"/> [SV] Specific version | <input type="checkbox"/> [FF] Free-free Interface | <input checked="" type="checkbox"/> [SI] Specific interface |

➤ AVAILABLE OPTIONS

- [SG] Strain gauges
- [ECS] Eddy current displacement sensor
- [NM] Non-magnetic
- [VAC] Vacuum